



PIN	FUNCTION	SYMBOL
1	VBL-	VBL-
2	VBL+	VBL+
3	VBL+	VBL+
4	VBL+	VBL+
5	NC	
6	RESET	
7	NC	
8	YU	
9	XR	
10	YD	
11	YU	
12	BO	
13	B1	
14	B2	
15	B3	
16	B4	
17	B5	
18	B6	
19	B7	
20	G0	
21	G1	
22	G2	
23	G3	
24	G4	
25	G5	
26	G6	
27	G7	
28	R0	
29	R1	
30	R2	
31	R3	
32	R4	
33	R5	
34	R6	
35	R7	
36	HSYNC	
37	VSYNC	
38	DOTCLK	
39	NC	
40	NC	
41	VCC	
42	VCC	
43	CS	
44	GND	
45	NC	
46	GND	
47	NC	
48	NC	
49	SCL	
50	SDI	
51	NC	
52	DEN	
53	GND	
54	GND	

- NOTE:
1. Display Type: 3.5" TFT, Transmissive
 2. Driver IC: NV3035
 3. Operating Temperature: -20°- +70°
 4. Storage Temperature: -30°- +80°
 5. Backlight Type: 6 White LEDs
 6. RoHS Compliant

TP Pin No.	Assignment
1	VDD(2.8V)
2	GND
3	INT(1.8V)
4	SCLK(1.8V)
5	SDATA(1.8V)
6	URAT(1.8V)

DLC Display Co., Limited
www.dlcdisplay.com

DRAWN BY:	TTITLE: DLC0350CZG-T-2	SCALE:	1:1
CHECKED BY:	DWG NO:	UNIT:	mm
APPROVED BY:	DWG NAME:	SHEET NO:	OF
CONFIRMED BY:			