


PIN	NAME
1	LEDK
2	LEDB
3	LEDB
4	LEDA
5	LEDA
6	G22+
7	G21+
8	G21-
9	G13+
10	G13-
11	VGH
12	VGL
13	G11+
14	G11-
15	G12+
16	G12-
17	VCI
18	VCI1
19	DV/DH
20	VCL
21	VREGOUT
22	VCOML
23	VCOMH
24	VCOM
25	VDD
26	VDDC
27	TE(PANAR)
28	CS
29	RS
30	WR/SCL
31	RD
32	SDI
33	DB0
34	DB1
35	DB2
36	DB3
37	DB4
38	DB5
39	DB6
40	DB7
41	DB8
42	DB9
43	DB10
44	DB11
45	DB12
46	DB13
47	DB14
48	DB15
49	DB16
50	DB17
51	DE
52	DCLK
53	HSYNC
54	VSYNC
55	RSSST
56	TV3
57	TV2
58	TV1
59	TV0
60	GND

DETAIL A (2:1)



DETAIL B (4:1)

- NOTES:**
1. DISPLAY TYPE: 3.5" TFT, TRANSMISSIVE
 2. VIEWING DIRECTION : U/L/D/R 55/65/65/65
 3. Driver IC : ILI9325C
 4. Top : -30° C ~ 85° C, Tst : -40° C ~ 90° C
 5. GENERAL TOLERANCE: ±0.2
 6. LCM Luminance: LED/650cd/m² (Typical)
 7. RoHS compliant

DLC Display Co., Limited
www.dlcdisplay.com

DRAWN BY:	TITLE: DLC0350YZQ
CHECKED BY:	SCALE:
APPROVED BY:	DWG NO:
CONFIRMED BY:	DWG NAME:
	SHEET NO: 0F
	UNIT: mm